



Updates on RPC first slot of intervention: RE3/1 installation

^{1,2} **E. Voevodina**, ³ **I. Crotty**, ^{2,3} **S. Buontempo**,
³ **B. Smiljkovic**

¹ *Universita Federico II di Napoli, 1-80125 Napoli,*

² *Istituto Nazionale di Fisica Nucleare (INFN), Sezione di Napoli,*

³ *European Organization for Nuclear Research, Geneva (Switzerland)*

Plan

- **Results of measurements of value “Z” for RE3/1;**
- **Fastening elements for fixing RE3/1 chambers on the YE3;**
- **Studies of the value “Z” for RE4/1;**
- **Mounting frames for RE4/1 chambers ;**
- **The proposal about mounting of the frames using mounting posts M24 (outer “R”)**


Four methods to determine the value "Z" for RE3/1

1. Main drawing of the CMS;
2. Manual measurements;
3. Laser scanner and laser tracker;
4. IR - sensors.

The value "Z" for RE3/1

1. Main drawing

➤ On basis the main drawing of the CMS the value "Z" for RE3/1 is **88 mm**!




Main parameters of assembly:

- distance between YE2 and YE3 = 655 mm;
- thickness of the neutron shielding = 63 mm;
- thickness of the one package of CSC = 504 mm;
- thickness of the RE3/1 = 25 mm;
- clearance between RE3/1 and shielding = 5 mm;
- clearance between RE3/1 chambers = 5 mm.


2. Manual measurements

The value "Z" for RE3/1

➤ The value "Z" for RE3/1 from manual measurements is **80 mm!**



* The features design of the CSC chamber were taken into account.






* Manual measurements in P5 was 19 of December 2016

The value "Z" for RE3/1

3. Laser scanner and laser tracker


* Laser scanning in P5 was done 19 of December 2016 (for YE-2 and YE-3 around the ME-3/1/13) and 10 of January 2017 (for YE+2 and YE+3 around the ME+3/1/13)



The value "Z" for RE3/1

Main results from laser scanner :

- Surfaces between YE-2 / / YE+2 and YE-3// +3 around the CSC chambers ME/-3/1/13 // ME/+3/1/13 (below the beam pipe on far side) have been measured;
- The topology of CSC chambers is determined very good;
- The average error of the best-fit is :
 - for YE/-2 and YE/-3 is +/-1.8 mm;
 - for YE/+2 and YE/+3 is +/-3.0 mm.
- The maximum error is :
 - for YE/-2 and YE/-3 is +/-2.5 mm;
 - for YE/+ 2and YE/+3 is +/-3.0 mm.
- The height of the collars are:
 - for YE/+3 is 19.6 mm;
 - for YE/+ 2 is 648.6 mm;
- The position of five M12 holes measured in the area of YE/+3 in front of the CSC chamber ME+3/1/13.



The value "Z" for RE3/1


4. IR sensors

* IR sensors were installed in 10th of January 2017

➤ Results will be come later after closing YE/+2 and YE/+3.


IR sensors with
individual
shielded cable

Target areas



Fastening elements for fixing RE3/1 chambers on the YE3

1. Mounting of the RE 3/1 chambers on the YE3




Each RE3/1 chamber is fixed in the six points





- Inner "R" of RE3/2 is 3302 mm;
- Outer "R" of RE31 is 3223 mm;
- Inner "R" of RE3/1 is 1546 mm;
- Outer "R" of the neutron shielding (cylindrical form) is 1526 mm .

Fastening elements for fixing RE3/1 chambers on the YE3

2. Mounting brackets for the RE 3/1 chambers





1, 2 and 3



Fastening elements for fixing RE3/1 chambers on the YE3

3. Mounting plates for the RE 3/1 chambers



Studies of the value “Z” for RE4/1

Available space for RE4/1 chambers

- On basis the main drawing of the CMS the value "Z" for RE4/1 is 85 mm.
- Perhaps in the real live the available space for RE4/1 chambers is about 80 mm. It isn't enough!

Because:

The space between ME4/1 and RE4/1 is about 15 mm or 20 mm;

Thickness of the RE4/1 “on” yoke is 25 mm;


Thickness of the RE4/1 “on” yoke is 25 mm;

The value gap is 5mm;


Thickness Alu mounting plates is 8 mm.

Total: **83 mm.**

Thus, we have the available space for RE4/1 chambers without overlap!







Mounting frames for RE4/1 chambers



The proposal about mounting of the frames using mounting posts M24 (outer “R”)

Two interesting questions:

1. How to mount the frame using the mounting positions M24?
2. How to attach the RE4/1 chambers on the frames?




Conclusion

- On the basis all received results we have the value “Z” for RE3/1 chambers 80 mm;
- The RE3/1 chambers brackets and mounting plates for fixing were produced;
- The drawings for brackets and mounting plates will be done in the end this week (Tuesday or Friday will be done);
- Next step will be study the mounting FEBs on the RE3/1 chambers;
- The available space for RE4/1 chambers is about 80 mm. It isn't enough for RE4/1 chambers with overlap;
- The mounting RE4/1 chambers frames were proposed (this exercise is going to be done).


Thanks for attentions!



Background

Scan YE/-2



Scan YE/-3






Available space for mounting FEBs

Available space for mounting FEBs is 68 mm

Cross section YE3



Space between RE3/2 and RE3/1 for the cooling/power connectors

